



Don't just Buy any Chimney

Because **80% of Buyers** choose the wrong one

MAKE NO MISTAKE

Call for a FREE Chimney Expert Consultation

Our expert visits your kitchen, analyzes the space,
and recommends exactly what you need.

WHY CHOOSE

KUTCHINA[®]
THE KITCHEN EXPERTS

20+ Years
of Expertise

Built for
Indian Kitchen

Service Support
within 24 Hours

State-of-the-Art
Manufacturing

Highest Warranty
in the Industry

Free Doorstep
Consultation

i-Auto Clean Chimneys



Sleek Gas Tablet



AO Water Healthifiers



Built-in Ovens



Dishwashers



PREMIUM RANGE OF PRODUCTS

PREMIUM CHIMNEYS

**AI-Powered
Auto Clean Technology**

**Intelligent
Heat Sensor**

**Low-Noise
Operation**

**100% Copper Motor
for Longer Life**

**Highest Consistent
Suction Performance**

**Wave Sensor
(Touchless Control)**



Angela Premium

75 | 90



Suction
1700±50m³/Hr

Noise Level
38 Db



Auto Clean Type : Intelligent Auto Clean
Total Power : 233 W
Switch Control : Touch Control with Wave Sensor
Outlet Diameter : 150 mm
Unit Dimension : L750/900 x W500 x H516 mm

Eleganza Premium

75 | 90



Suction
1800±50m³/Hr

Noise Level
48 Db



Auto Clean Type : Intelligent Auto Clean
Total Power : 298 W
Switch Control : Touch Control with Wave Sensor
Outlet Diameter : 150 mm
Unit Dimension : L750/900 x W500 x H570 mm

Veronica Premium

75 | 90



Suction
1600±50m³/Hr

Noise Level
48 Db



Auto Clean Type : 3rd Gen Dry AutoClean
Total Power : 233 W
Switch Control : Touch Control with Wave Sensor
Outlet Diameter : 150 mm
Unit Dimension : L750/900 x W500 x H516 mm

Nora Premium

75 | 90



Suction
1600±50m³/Hr


Noise Level
38 Db



Auto Clean Type : Intelligent Auto Clean
Total Power : 193 W
Switch Control : Touch Control
Outlet Diameter : 150 mm
Unit Dimension : L750/890 x W456 x H479.5 mm

Silvia Premium

75



Suction
1600±50m³/Hr

Noise Level
48 Db



Auto Clean Type : Intelligent Auto Clean
Total Power : 257 W
Switch Control : Touch Control with Wave Sensor
Outlet Diameter : 150 mm
Unit Dimension : L745 x W340 x H850 mm

Melody Premium

60 | 75 | 90



Suction
1500±50m³/Hr

Noise Level
38 Db



Auto Clean Type : Intelligent Auto Clean
Total Power : 183 W
Switch Control : Touch Control with Wave Sensor
Outlet Diameter : 150 mm
Unit Dimension : L595/750/868 X W420 X H472 mm

Cherry Premium

75



Suction
1400±50m³/Hr

Noise Level
48 Db



Auto Clean Type : 3rd Gen Dry AutoClean
Total Power : 248 W
Switch Control : Touch Control with Wave Sensor
Outlet Diameter : 150 mm
Unit Dimension : L760 X W500 X H120 mm

Mario Premium

75 | 90



Suction
1400±50m³/Hr

Noise Level
48 Db



Auto Clean Type : 3rd Gen Dry AutoClean
Total Power : 186 W
Switch Control : Touch Control with Wave Sensor
Outlet Diameter : 150 mm
Unit Dimension : L750/900 x W415 x H355 mm

BLDC MOTORS

Siena Premium

75 | 90



Suction
1600±50m³/Hr

Noise Level
32 Db



Auto Clean Type : Intelligent Auto Clean
Total Power : 163 W
Switch Control : Touch Control with Wave Sensor
Outlet Diameter : 150 mm
Unit Dimension : L750/868 x W420 x H472 mm

Lorita Premium

75 | 90



Suction
1700±50m³/Hr

Noise Level
32 Db



Auto Clean Type : Intelligent Auto Clean
Total Power : 163 W
Switch Control : Touch Control with Wave Sensor
Outlet Diameter : 150 mm
Unit Dimension : L750/890 x W456 x H479.5 mm

Lavender Premium

75 | 90



Suction
1600±50m³/Hr

Noise Level
42 Db



Auto Clean Type : Intelligent Auto Clean
Total Power : 163 W
Switch Control : Touch Control with Wave Sensor
Outlet Diameter : 160 mm
Unit Dimension : L750/900 x W450 x H510 mm

PREMIUM HEALTHIFIERS

Anti Oxidant Technology

Back Wash for Self Cleaning

Lowest Maintenance Cost

VEDICAA DLX PLUS PREMIUM

TECHNICAL SPECIFICATIONS

Storage Tank Capacity	7 L
Membrane Type	TFC
Purification Stages	11 Stage Purification
TDS Reduction	90 - 95%
TDS Controller	Yes
Antioxidant + Mineral	Yes
Production Capacity	7.8 - 15 L/Hr
Indicators	Digital Display
Water Inlet Pressure	≥ 0.2 kg/cm ²
AC Mains	230V - 50Hz
Backwash / Autoclean	Yes
Activate Copper Candle	Yes



RO+UV+UF

VEDICAA EXCEL PLUS PREMIUM

TECHNICAL SPECIFICATIONS

Storage Tank Capacity	7 L
Membrane Type	TFC
Purification Stages	11 Stage Purification
TDS Reduction	90 - 95%
TDS Controller	Yes
Antioxidant + Mineral	Yes
Production Capacity	7.8 - 15 L/Hr
Indicators	LED Indicator
Water Inlet Pressure	≥ 0.2 kg/cm ²
AC Mains	230V - 50Hz
Backwash / Autoclean	Yes
Activate Copper Candle	Yes



RO+UV+UF

PURICA EXCEL

TECHNICAL SPECIFICATIONS

Storage Tank Capacity	7 L
Membrane Type	TFC
Purification Stages	9 Stage Purification
TDS Reduction	90 - 95%
TDS Controller	Yes
Antioxidant + Mineral	Yes
Production Capacity	7.8 - 15 L/Hr
Indicators	NA
Water Inlet Pressure	≥ 0.2 kg/cm ²
AC Mains	230V - 50Hz
Backwash	Yes
Activate Copper Candle	No



RO+UV

PURICA

TECHNICAL SPECIFICATIONS

Storage Tank Capacity	7 L
Membrane Type	TFC
Purification Stages	8 Stage Purification
TDS Reduction	90 - 95%
TDS Controller	N/A
Antioxidant + Mineral	Yes
Production Capacity	7.8 - 15 L/Hr
Indicators	NA
Water Inlet Pressure	≥ 0.2 kg/cm ²
AC Mains	230V - 50Hz
Backwash	Yes
Activate Copper Candle	No



RO

PURICA ECO PREMIUM

TECHNICAL SPECIFICATIONS

Storage Tank Capacity	5 L
Membrane Type	TFC
Purification Stages	8 Stage Purification
TDS Reduction	90 - 95%
Antioxidant + Mineral	Yes
Production Capacity	7.8 - 15 L/Hr
Water Inlet Pressure	≥ 0.2 kg/cm ²
AC Mains	230V - 50Hz



PURICA UV PREMIUM

TECHNICAL SPECIFICATIONS

Storage Tank Capacity	5 L
Purification Stages	5 Stage Purification
Antioxidant + Mineral	Yes
Production Capacity	700ml - 1 L/Min
Water Inlet Pressure	≥ 0.2 kg/cm ²
AC Mains	230V - 50Hz



PURICA UNDER SINK RO



Storage Tank Capacity	15 L
Membrane Type	TFC
TDS Reduction	90 - 95%
TDS Controller	Yes

Purification Stages	7.8 - 15 L/Hr
Production Capacity	5 Stage Purification
Water Inlet Pressure	≥ 0.2 kg/cm ²
AC Mains	230V - 50Hz

PREMIUM GAS APPLIANCES

Aesthetic Design

Zero Gas Wastage

Jumbo Burner

Heavy Duty

TABLET 2B 3B 4B



TECHNICAL SPECIFICATIONS

Burner Type	: Brass Burner
Burner Spreader	: Aluminium
Burner Size	: 110 mm, 90 mm, 70 mm
Burner Power	: 110mm - 3.0 Kw 90mm - 2.0 Kw 70mm - 1.5 Kw
Ignition (Battery 1.5V)	: Pulse Ignition
Gas Type	: Both LPG and NG
Glass	: 6mm Tempered Glass
Pan Support Type	: Cast Iron (Matte Finish)
Product Dimension	: L760 X W450 X H30 mm

EMBER 3B

TECHNICAL SPECIFICATIONS

Burner Type	Brass Burner	Burner Format	With Inner/Outer Locking
Burner Base	Aluminium Alloy	Pan Support	Thick Euro-coated
Burner Size	79/69/92		



EMBER 2B

TECHNICAL SPECIFICATIONS

Burner Type	Brass Burner	Burner Format	With Inner/Outer Locking
Burner Base	Aluminium Alloy	Pan Support	Thick Euro-coated
Burner Size	69/79		



Smart Built-ins



IMPRESSO

Capacity	65 L
Rated Input Voltage	230V~50Hz
Switch Control	Mechanical Timer
Cooking Function	9
Grill Power Consumption	2.2Kw
Oven Power Consumption	2250W
Child Lock	N/A
Cooking Timer	2Hrs



KLEANMATE EXCEL

Place Setting	14
Modes	7
Rated Input Voltage	230 V 50 Hz
Switch Control	Push Button
Child Lock	Yes
Delay Function	Max. 24 Hrs
½ Load Function	Yes
Water Consumption	3080 L
Installation Type	Free Standing



BLAZE DLX

Capacity	70 L
Rated Input Voltage	230V~50Hz
Switch Control	Feather Touch
Cooking Function	9
Grill Power Consumption	2.2Kw
Oven Power Consumption	2250W
Child Lock	Yes
Cooking Timer	9Hrs



KLEANMATE ECO

Place Setting	12
Modes	6
Rated Input Voltage	230 V 50 Hz
Switch Control	Push Button
Digital Display	LED Indicator
Delay Function	Max. 9 Hrs
½ Load Function	Yes
Water Consumption	3080 L
Installation Type	Free Standing



DAZZLE

Capacity	22 L
Rated Input Voltage	230V~50Hz
Switch Control	Mechanical Timer
Auto Cook Menu	8
Grill Power Consumption	1Kw
Child Lock	Yes
Cooking Timer	95Mins
Input & Output Power (Microwave)	1250W (In) & 800W (Out)



KEN DLX

Place Setting	12
Modes	6
Rated Input Voltage	230 V 50 Hz
Switch Control	Push Button
Digital Display	N/A
Delay Function	Max. 9 Hrs
½ Load Function	Yes
Water Consumption	3080 L
Installation Type	Semi Built-in



RADIANZ

Capacity	25 L
Rated Input Voltage	230V~50Hz
Switch Control	Feather Touch
Auto Cook Menu	10
Grill Power Consumption	1.1Kw
Convection Power Consumption	2250W
Child Lock	Yes
Cooking Timer	95Mins



KEN ECO

Place Setting	8
Modes	6
Rated Input Voltage	230 V 50 Hz
Switch Control	Push Button
Digital Display	LED Indicator
Delay Function	Max. 8 Hrs
½ Load Function	N/A
Water Consumption	2240 L
Installation Type	Counter Top